(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 8 July 2004 (08.07.2004)

PCT

(10) International Publication Number WO 2004/057286 A1

(51) International Patent Classification⁷: C21C 5/46

G01J 5/04,

(21) International Application Number:

PCT/EP2003/012349

(22) International Filing Date:

5 November 2003 (05.11.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

102 59 830.4


19 December 2002 (19.12.2002) DE

(71) Applicant (for all designated States except US): SPE-CIALTY MINERALS MICHIGAN INC. [US/US]; 30600 Telegraph Road, Bingham Farms, MI 48025 (US).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CARLHOFF, Christoph [DE/DE]; Am Sandacker 12, 47877 Willich (DE). MERKENS, Wilhelm [DE/DE]; Krickelberg 89, 41836 Hückelhoven (DE). LAMM, Rolf [DE/DE]; Graf-Schwerin-Strasse 44, 52066 Aachen (DE).
- (74) Agents: JANSSEN, Bernd et al.; Uexküll & Stolberg, Beselerstrasse 4, 22607 Hamburg (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: A PROCESS FOR KEEPING A TUYERE PASSING THROUGH A METALLURGICAL VESSEL FREE OF A SKULL



Light path of 3 unobstructed

$$\begin{array}{l} I_{(1)} \to T_{(1)} \\ I_{(2)} \to T_{(2)} \\ I_{(Q)} \to T_{(Q)} \\ T_{(1)} = T_{(2)} = T_{(Q)} \end{array}$$

Light path of 3 obstructed

$$I_{(1)} \to T_{(1)}$$

$$I_{(2)} \to T_{(2)}$$

$$I_{(Q)} \to T_{(Q)}$$

$$T_{(1)} = T_{(2)} \neq T_{(Q)}$$

(57) Abstract: The present invention relates to a process for keeping a tuyere passing through a metallurgical vessel free of a skull by intermittendly passing an oxygen-containing gas through the tuyere to dissolve the skull, wherein it is determined that an interval for passing said oxygen-containing gas through the tuyere needs to be started by detecting electromagnetic radiation emanating from a spot in the interior of the melt by means of a dual wavelength pyrometer and comparing the intensity of the pyrometer signals with the ratio of the pyrometer signals, and initiating said intervall for passing said oxygen-containing gas through the tuyere, upon the condition that the combined intensity of the signals falls below a predetermined threshold value and that the ratio of the signals remains substantially constant.

WO 2004/057286 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.